



NCDOH



- 540 TVL Horizontal Resolution
- Electronic Iris
- Day & Night
- 3 Axis Built in Dome Housing
- High Sensitivity



NCDOH: 3 Axis Dome Camera

CCD Type	1/3"SONY CCD	1/3"SONY CCD	1/3"SONY CCD	SHARP	1/4"SHARP
Pixels	PAL:795×596 NTSC:811×508	PAL:752×582 NTSC:768×494	PAL:500×582 NTSC:510×492		
Horizontal Resolution	540TVL	480TVL	420TVL	420TVL	420TVL
Scanning System	PAL / NTSC				
Level Synchronization frequency	PAL:15.625KHZ / NTSC:15.734KHZ				
Clock frequency	PAL:19.3125 / NISC:19.0699				
Scanning System	2:1 Deinterlacing				
Minimum illumination	0.01LUX	0.1LUX	0.01LUX	0.1LUX	0.1LUX
Sync. System	Synchronization				
S/N Ratio	48 dB				
Electronic Shutter	PAL:1/50-1/100,000sec;NTSC:1/60-1/100,000				
Gamma Correction	0.45				
Video Output	1 Vpp,75 Ohms				
AGC	Auto				
Night Vision	non				
Power supply	12VDC (+/-10%)				
Current	150mA				
Lens	3.5 to 10mm Varifocal				
Dimensions	127x127x43 mm				
Weight	0.36Kg				
Operating temperature	-10-45°C				
Color	White				

