



**Economical...
Effective....
Efficient...**

**Everything under one roof
to protect
what is under your roof!**

**Reliability you've
come to expect
from the industry's
leader in fire alarm
technology.**



**SMPS
Power
Supply**



www.qualitronix.com

An ISO 9001-2000 Certified Company



FEATURES:

1. Designed as per IS 2189 specifications
2. User friendly in handling the panel.
3. SMPS power supply with inbuilt battery charger.
4. Operates on 12VDC.
5. 16x2 LCD display to indicate zone status such as loop open, loop short circuit, fire, zone isolation, alarm acknowledgment and low battery.
6. LED indications for AC On, System on Battery, DC fuse, Charger fuse and Fire.
7. Control switches for zone isolation, alarm acknowledgment and system reset.
8. Internal Buzzer for warning – zone short, low battery and alarm acknowledged.
9. Auto-Dialer connectivity.
10. Hooter audibility is 90dB @ 1 meter.
11. 48 hrs battery back up
12. Easy Installation and maintenance (modular type circuit boards).

FIRE ALARM

SPECIFICATION:

Input voltage	: 230 V A.C
Zone Voltage	: 12 V DC
Power consumption	: 20W @230 V AC.
Quiescent current	: 70 mA @ 12 V DC.
Alarm current	: 300 mA @ 12 V DC.



NEW NO. 30 (OLD NO. 31), 18TH AVENUE, ASHOK NAGAR,
CHENNAI 600 083, TAMIL NADU.
TELEFAX: +91-44-24713888 (5Lines)
EMAIL: sales@qualitronix.com



www.qualitronix.com

An ISO 9001-2000 Certified Company